



Corporate Office: Adelaide, Australia

Contact Us: Office: +61 8 7099 4600

Fax: +61 8 8132 0543

info@trackiq.com.au

www.trackiq.com.au

- FleetONE system benefits include:**
- Integrates with your maintenance system to generate work orders
 - Web application delivered
 - Intuitive functions
 - Advanced search function
 - Password protection
 - System expandable
 - Help desk support
 - Role based privileges and administration
 - Standard reporting functions including:
 - Alerts
 - Component history
 - Vehicle mimic
 - Train load profile
 - Axle mass
 - Wheel condition
 - Bearing conditions
 - “Worst” wheel/vehicle by sensor class.

FleetONE

Imports, aggregates and unifies critical wayside rolling stock data.

Track IQ has developed the FleetONE software platform to unify all of your wayside monitoring data into a single system. FleetONE presents a holistic set of views of the data – from individual component measurement and trends through to fleet-wide metrics.

FleetONE seamlessly allows the rolling stock manager to access all stored data on rolling stock, and receive alerts and reports based on sensor measurements. Track IQ lead products, RailBAM® and WCM® provide data feeds into FleetONE.

FleetONE also supports data feeds from other wayside detectors including Wheel Profile, HADB, HWD, WILD and Brake Shoe Wear.

Advanced search and reporting functions enable the rapid identification of condition monitoring faults – and these faults can be automatically raised as work orders in an external maintenance system such as SAP.

Proprietary software is not required for your multi-user work stations as FleetONE is delivered as a web based application – key personnel will have access to FleetONE via their web browser.



Corporate Office: Adelaide, Australia

Contact Us: Office: +61 8 7099 4600

Fax: +61 8 8132 0543

info@trackiq.com.au

www.trackiq.com.au

Fleet ONE Train List												
Date/Quality	Train Time	Site	Sensor Type	Direction	Entry Speed (km/h)	Exit Speed (km/h)	Vehicle Count (Inc./Sec)	Axle Count	Length (m)	Highest Bearing Fault	Highest Bearing Alert	
5/11/2014 22:15:09	Passenger Down	RAILBAM	North	94	93	12	48	241	RS3			
5/11/2014 22:12:15	Passenger Up	RAILBAM	South	46	46	6	24	135	RS3			
5/11/2014 22:10:15	Passenger Down	RAILBAM	North	87	86	8	32	159	RS2 p			
5/11/2014 22:09:59	Passenger Up	WCM2	South	60	60	8	32	158				
5/11/2014 22:09:11	Passenger Up	RAILBAM	South	60	60	8	32	159	RS3			
5/11/2014 22:07:58	Passenger Down	RAILBAM	North	75	76	6	24	135	RS3			
5/11/2014 22:02:00	Passenger Down	RAILBAM	North	26	24	12	48	241	RS3			

Feature Rich User Interface

The FleetONE user interface features a customisable set of data views – allowing the user to sort, filter, resize and enable/disable all data-grid columns.

FleetONE supports multiple languages, both metric and imperial measurements, and user assigned profiles and privileges.

FleetONE General Specifications

Summary and History Lists	The “Train List” presents a list of trains that have passed all sensor sites. From this view, the user can navigate to summaries of the train by vehicle, axle and bearing/wheel. These views show all measurements and alerts recorded for that train pass. From there, users can select individual component records and navigate to show the measurement history of that component.
Graphs	Per component trend graphs – for RailBAM, Wheel profile, WILD and HBD data.
	Per train graphs – axle load profile, STS and ETE imbalance profile, HBD temperature profile.
	Fleet reports – HBD alarm summaries by time, histograms for wheel profile and RailBAM statistics.
	All graphs support dynamic modification of time ranges and other input parameters.
Maintenance System Integration	Maintenance planners are provided with tools that allow them to search for and retrieve the set of components with measured defects. Planners can then raise those defects in external systems (e.g. SAP) as work orders, at the click of a button.
Log in	Password protection via FleetONE local password or Windows Active Directory login.
Configurable alert levels	WILD: Vehicle and axle weight overload alerts. Vehicle STS and ETE imbalance alerts, Wheel Impact Alerts – peak force, impact ratio.
	Acoustic Bearing Monitor: Defect classifications are grouped to determine alert levels
	Brake Shoe Wear alert
	Wheel profile: flange, rim, hollow
	HBD: Hot Bearing/Hot Wheel alarms retrieved from the remote site and displayed
Data health	Shows trends and alerts on wayside detector status – last communication time, quality of data.
Data protection	Users associated with owner/operator organisations are restricted to viewing measurement data for vehicles that belong to that organisation.

Specifications are subject to change without notice.
ONEJuly14 Export Issue